

Safety Data Sheet
according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

1 Identification

- **Other means of identification**
- **Trade name:** FloorPro Tyre and Abrasion Marks Remover RM 776
- **Relevant identified uses of the substance or mixture and uses advised against**
Restricted to professional users.
- **Application of the substance / the mixture** Detergent
- **Uses advised against** –
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

Alfred Kärcher SE & Co. KG
Alfred-Kärcher-Str. 28-40
D - 71364 Winnenden
Tel.: +49-7195-14-0

Kärcher Pty. Ltd.
385 Ferntree Gully Rd
Mount Waverley, Victoria 3149
Victoria
Ph.: +61-3-9765-2300

Internet: www.karcher.com
- **Distributor:**
Kärcher Pty. Ltd.
385 Ferntree Gully Rd
Mount Waverley, Victoria 3149
Victoria
Ph.: +61-3-9765-2300
www.karcher.com.au
- **Email competent person:** productsafety.management@de.karcher.com
- **Further information obtainable from:**

Regulatory Affairs
Tel.: +49-7195-14-0
productsafety.management.de@karcher.com
- **Emergency telephone number:**

For Hazardous Materials [or Dangerous Goods] Incidents
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

2 Hazard(s) Identification

- **Classification of the substance or mixture**
Corrosive to metals – Category 1 H290 May be corrosive to metals.
Skin corrosion/irritation – Category 1C H314 Causes severe skin burns and eye damage.

(Contd. on page 2)

Safety Data Sheet according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 1)

Eye damage/irritation – Category 1 H318 Causes serious eye damage.

Label elements

GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms

Corrosion



GHS05

Signal word Danger

Hazard-determining components of labelling:

sodium hydroxide (≥ 0.5 - < 2 %)

Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition and Information on Ingredients

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:

112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye damage/irritation – Category 2A, H319	10-20%
15763-76-5	sodium p-cumenesulphonate ⚠ Eye damage/irritation – Category 2A, H319	1-5%
1310-73-2	sodium hydroxide ⚠ Corrosive to metals – Category 1, H290; Skin corrosion/irritation – Category 1A, H314; Eye damage/irritation – Category 1, H318 Specific concentration limits: Skin corrosion/irritation – Category 1A; H314: $C \geq 5$ % Skin corrosion/irritation – Category 1B; H314: $2 \% \leq C < 5$ % Skin corrosion/irritation – Category 2; H315: $0.5 \% \leq C < 2$ % Eye Irrit. 2; H319: $0.5 \% \leq C < 2$ %	≥ 0.5 - < 2 %
31726-34-8	hexane-1-ol, ethoxylated (polymer) ⚠ Eye damage/irritation – Category 1, H318; ⚠ Acute toxicity - oral – Category 4, H302 Specific concentration limits: Eye damage/irritation – Category 1; H318: $C \geq 15$ % Eye Irrit. 2; H319: $C \geq 99$ %	1-5%

(Contd. on page 3)

Safety Data Sheet
according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 2)

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- **General information**
Involve doctor immediately.
Immediately remove any clothing soiled by the product.
- **After inhalation**
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.
- **After skin contact** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed** Corneal damage
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Suitable extinguishing agents**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Hazchem Code:** 2R
- **Protective equipment:** Wear fully protective suit.
- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Safety Data Sheet according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 3)

Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

Handling
Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with eyes and skin.

Information about fire - and explosion protection: No special measures required.

Storage
Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility:

Do not store together with acids.

Keep away from food, beverages and feed.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

Appropriate engineering controls No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:
1310-73-2 sodium hydroxide

WES | Peak limitation: 2 mg/m³
DNELs
15763-76-5 sodium p-cumenesulphonate

Oral	DNEL	3.8 mg/kg×d (consumer)
Dermal	DNEL	136.25 mg/kg×d (employee)
		68.1 mg/kg×d (consumer)
Inhalative	DNEL	26.9 mg/m ³ (employee)
		6.6 mg/m ³ (consumer)

(Contd. on page 5)

Safety Data Sheet according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 4)

1310-73-2 sodium hydroxide

Inhalative	DNEL	1 mg/m ³ (employee)
		1 mg/m ³ (consumer)

· PNECs

15763-76-5 sodium p-cumenesulphonate

PNEC	0.23 mg/l (freshwater)
	0.023 mg/l (marine water)
	100 mg/l (STP)
PNEC sediment	0.862 mg/kg (freshwater)
	0.086 mg/kg (marine water)
PNEC soil	0.037 mg/kg (soil)

· Personal protective equipment

· General protective and hygienic measures

Do not inhale gases / fumes / aerosols.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Filter A/P2.

· Protection of hands:



Protective gloves.

· Material of gloves Butyl rubber, BR

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

* butyl rubber 0,7 mm, 480 min (EN 374)

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Nitrile rubber, NBR

· Eye protection:



Tightly sealed goggles (EN 166)

· Body protection:

Boots
Apron

AU

(Contd. on page 6)

Safety Data Sheet according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 5)

9 Physical and Chemical Properties

· General Information	
· Appearance:	
· Form:	Fluid
· Colour:	Light yellow
· Odour:	fresh
· Odour threshold:	Not determined
· pH-value at 20 °C:	13
· pH-value 1 %:	10-12
· Change in condition	
· Melting point/freezing point:	-7 °C
· Initial boiling point and boiling range:	100 °C
· Flash point:	Not applicable
· Flammability (solid, gaseous)	Not applicable
· Auto-ignition temperature:	not applicable
· Decomposition temperature:	Not determined
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	Not determined
· Upper:	Not determined
· Vapour pressure:	Not determined
· Density at 20 °C:	1.063 g/cm ³
· Relative density	Not determined
· Vapour density	Not determined
· Evaporation rate	Not determined
· Solubility in / Miscibility with	
· Water:	Fully miscible
· Partition coefficient: n-octanol/water:	Not determined
· Viscosity:	
· dynamic at 20 °C:	3 mPas
· kinematic:	Not determined
· Solvent content:	
· Solids content:	19.6 %
· Other information	
· Additional information	
· Particle characteristics	Not applicable
· Physical state	Liquid

10 Stability and Reactivity

- **Reactivity** corresponds to 10.3

(Contd. on page 7)

Safety Data Sheet according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 6)

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
 - Corrosive action on metals
 - Reacts with strong acids
 - Strong exothermic reaction with acids
 - Reacts with light alloys to form hydrogen
 - Corrodes aluminium
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Not compatible with alkali-sensitive substances like Sn, Zn, Al and paintings.
- **Hazardous decomposition products:** No dangerous decomposition products known

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

112-34-5 2-(2-butoxyethoxy)ethanol

Oral	LD50	2410 mg/kg (mouse) (OECD 401)
Dermal	LD50	2764 mg/kg (Rabbit)

15763-76-5 sodium p-cumenesulphonate

Oral	LD50	>5000 mg/kg (Rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (Rabbit)

31726-34-8 hexane-1-ol, ethoxylated (polymer)

Oral	LD50	>300-2000 mg/kg (Rat)
------	------	-----------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

AU

(Contd. on page 8)

Safety Data Sheet

according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 7)

12 Ecological Information

· Toxicity

· Aquatic toxicity:

112-34-5 2-(2-butoxyethoxy)ethanol

LC50/96 h	1300 mg/l (Lepomis macrochirus)
EC10/16 h	1170 mg/l (Pseudomonas putida)
EC50/24 h	2850 mg/l (Daphnia magna) (DIN 38412)
NOEC	>100 mg/l (Desmodesmus subspicatus)

15763-76-5 sodium p-cumenesulphonate

LC50/96 h (static)	>100 mg/l (Oncorhynchus mykiss)
EC50/48 h (static)	>100 mg/l (Daphnia magna)
EC50/96 h (static)	>100 mg/l (Pseudokirchneriella subcapitata)

1310-73-2 sodium hydroxide

LC50/96 h	125 mg/l (Gambusia affinis)
EC50/48 h	76 mg/l (Daphnia magna)
	40.4 mg/l (Ceriodaphnia dubia)
EC50/15 min	22 mg/l (Photobacterium phosphoreum)

· Persistence and degradability No further relevant information available.

· Degree of elimination:

112-34-5 2-(2-butoxyethoxy)ethanol

OECD 301C	80-90 % (28 d)
OECD 301E	>70 % (28 d)
OECD 302B	100 % (28 d)

· Behaviour in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

The product does not contain organically bounded halogens (AOX-free).

The contained organic complexing agents reach a DOC-elimination grade of 80% (corresponding to No. 406 of Annex "Analytic and measuring methods") and with this meet the tightened demands of Annex 49 of the revised Directive on liquid waste.

(Contd. on page 9)

Safety Data Sheet according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 8)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable

· **vPvB:** Not applicable

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Must be specially treated adhering to official regulations.

· Uncleaned packaging:

· Recommendation:

Non contaminated packagings may be recycled.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· **Recommended cleansing agents:** Water, if necessary together with cleaning agents.

14 Transport information

· UN-Number

· ADG, IMDG, IATA

UN1824

· UN proper shipping name

· ADG

1824 SODIUM HYDROXIDE SOLUTION

· IMDG, IATA

SODIUM HYDROXIDE SOLUTION

· Transport hazard class(es)

· ADG



· Class

8 (C5) Corrosive substances.

(Contd. on page 10)

Safety Data Sheet according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 9)

· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances.
· Label	8
· Packing group	
· ADG, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances.
· Hazard identification number (Kemler code):	80
· Hazchem Code:	2R
· EMS Number:	F-A, S-B
· Segregation groups	(SGG18) Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable
· Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1824 SODIUM HYDROXIDE SOLUTION, 8, III

AU

(Contd. on page 11)

Safety Data Sheet according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 10)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Industrial Chemicals

7732-18-5	water
112-34-5	2-(2-butoxyethoxy)ethanol
164462-16-2	methylglycine diacetic acid, trisodium salt, solution
1310-73-2	sodium hydroxide
31726-34-8	hexane-1-ol, ethoxylated (polymer)
68154-97-2	fatty alcohol C10-C12, ethoxylated, propoxylated
5182-36-5	2,4,6-trimethyl-4-phenyl-1,3-dioxane
18479-58-8	Dihydromyrcenol
54464-57-2	1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone
77-54-3	Cedryl acetate
80-56-8	alpha-Pinene
115-95-7	linalyl acetate
127-91-3	beta-pinene
470-82-6	eucalyptol
1205-17-0	alpha-methyl-1,3-benzodioxole-5-propionaldehyde
4180-23-8	trans-Anethole
14073-97-3	l-Menthone
73018-51-6	1,6-Octadien-3-ol, 3,7-dimethyl-, acid-isomerized
106-22-9	dl-Citronellol
5989-27-5	(R)-p-mentha-1,8-diene

· Standard for the Uniform Scheduling of Medicines and Poisons

112-34-5	2-(2-butoxyethoxy)ethanol	S5
1310-73-2	sodium hydroxide	S5, S6, S10
470-82-6	eucalyptol	S6

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

· National regulations

· **Information about limitation of use:** Employment restrictions concerning juveniles must be observed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
A product information sheet can be provided if requested.

(Contd. on page 12)

AU

Safety Data Sheet
according to WHS Regulations

Date of issue: 30.01.2026

Version number 8

Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 11)

Relevant phrases

- H290 May be corrosive to metals.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

Contact:

Regulatory Affairs
Tel.: +49-7195-14-0
productsafety.management.de@karcher.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Corrosive to metals – Category 1: Corrosive to metals – Category 1
Acute toxicity - oral – Category 4: Acute toxicity – Category 4
Skin corrosion/irritation – Category 1A: Skin corrosion/irritation – Category 1A
Skin corrosion/irritation – Category 1C: Skin corrosion/irritation – Category 1C
Eye damage/irritation – Category 1: Serious eye damage/eye irritation – Category 1
Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

Sources*** Data compared to the previous version altered.**

0-011-343-0 RM776/5 2-613