

Safety Data Sheet
according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

1 Identification

- **Other means of identification**
- **Trade name:** VehiclePro Klear!Glow RM 894
- **Relevant identified uses of the substance or mixture and uses advised against**
Restricted to professional users.
- **Application of the substance / the mixture** Drying aid for vehicle washing plants
- **Uses advised against** –
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

Alfred Kärcher SE & Co. KG
Alfred-Kärcher-Str. 28-40
D - 71364 Winnenden
Tel.: +49-7195-14-0

Kärcher Pty. Ltd.
385 Ferntree Gully Rd
Mount Waverley, Victoria 3149
Victoria
Ph.: +61-3-9765-2300

Internet: www.karcher.com
- **Distributor:**
Kärcher Pty. Ltd.
385 Ferntree Gully Rd
Mount Waverley, Victoria 3149
Victoria
Ph.: +61-3-9765-2300
www.karcher.com.au
- **Email competent person:** productsafety.management@de.karcher.com
- **Further information obtainable from:**

Regulatory Affairs
Tel.: +49-7195-14-0
productsafety.management.de@karcher.com
- **Emergency telephone number:**

For Hazardous Materials [or Dangerous Goods] Incidents
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

2 Hazard(s) Identification

- **Classification of the substance or mixture**
Skin corrosion/irritation – Category 2 H315 Causes skin irritation.

(Contd. on page 2)

Safety Data Sheet according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

Trade name: VehiclePro Klear!Glow RM 894

(Contd. of page 1)

Eye damage/irritation – Category 1 H318 Causes serious eye damage.

Label elements

GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms

Corrosion



GHS05

Signal word Danger

Hazard-determining components of labelling:

1-propanaminium, 2-hydroxy-N-(2-hydroxypropyl) -N-N-dimethyl, diesters with vegetable oil fatty acids, methyl sulfates (≥5- <10 %)

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

3 Composition and Information on Ingredients

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:

112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Eye damage/irritation – Category 2A, H319	≥5-<10%
1474044-71-7	1-propanaminium, 2-hydroxy-N-(2-hydroxypropyl) -N-N-dimethyl, diesters with vegetable oil fatty acids, methyl sulfates ⚠ Eye damage/irritation – Category 1, H318; ⚠ Skin corrosion/irritation – Category 2, H315	≥5-<10%
9004-78-8	Phenol, ethoxylated ⚠ Acute toxicity - oral – Category 4, H302	5-10%
1335203-21-8	Imidazolium compounds, 2-C17-unsatd.-alkyl-1-(2-C18-unsatd. amidoethyl)-4,5-dihydro-N-methyl, Me sulfates ⚠ Skin corrosion/irritation – Category 2, H315; Eye damage/irritation – Category 2A, H319	≥1-<2.5%
14858-73-2	Bis(2-ethylhexyl)carbonate ⚠ Skin corrosion/irritation – Category 2, H315	1-5%

(Contd. on page 3)

AU

Safety Data Sheet
according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

Trade name: VehiclePro Klear!Glow RM 894

(Contd. of page 2)

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact** Generally the product does not irritate the skin.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.
- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Suitable extinguishing agents**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Protective equipment:** No special measures required.
- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
Do not allow to penetrate the ground/soil.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

AU

(Contd. on page 4)

Safety Data Sheet according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

Trade name: **VehiclePro Klear!Glow RM 894**

(Contd. of page 3)

7 Handling and Storage

- **Handling**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Avoid contact with eyes and skin.
- **Information about fire - and explosion protection:** No special measures required.
- **Storage**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Keep away from food, beverages and feed.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Appropriate engineering controls** No further data; see section 7.
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· PNECs

1474044-71-7 1-propanaminium, 2-hydroxy-N-(2-hydroxypropyl) -N-N-dimethyl, diesters with vegetable oil fatty acids, methyl sulfates

PNEC	10 mg/l (STP) (Assessment factor: 100)
PNEC sediment	1.7 mg/kg (freshwater) (sediment dw) 0.17 mg/kg (marine water) (sediment dw)
PNEC aqua	0.017 mg/l (freshwater) (Assessment factor: 10) 0.002 mg/l (marine water) (Assessment factor: 100)

- **Personal protective equipment**
- **General protective and hygienic measures**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Protection of hands:**



Protective gloves.

- **Material of gloves** Butyl rubber, BR
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety Data Sheet
according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

Trade name: VehiclePro Klear!Glow RM 894

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles (EN 166)

9 Physical and Chemical Properties

· General Information

· Appearance:

- Form: Fluid
- Colour: Red
- Odour: Pine
- Odour threshold: Not determined.
- pH-value at 20 °C: 4.1
- pH-value 1 %: 5-7
- Change in condition
- Melting point/freezing point: 0 °C
- Initial boiling point and boiling range: undetermined
- Flash point: Not applicable
- Flammability (solid, gaseous) Not applicable.
- Auto-ignition temperature: not applicable
- Decomposition temperature: Not determined.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Product does not present an explosion hazard.
- Explosion limits:
- Lower: Not determined.
- Upper: Not determined.
- Vapour pressure: Not determined.
- Density at 20 °C: 1.0058 g/cm³
- Relative density Not determined.
- Vapour density Not determined.
- Evaporation rate Not determined.
- Solubility in / Miscibility with
- Water: Fully miscible
- Partition coefficient: n-octanol/water: Not determined.
- Viscosity:
- dynamic: Not determined.
- kinematic: Not determined.

- Other information No further relevant information available.
- Additional information
- Particle characteristics Not applicable.

(Contd. on page 6)

Safety Data Sheet
according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

Trade name: VehiclePro Klear!Glow RM 894

(Contd. of page 5)

Physical state	Liquid
----------------	--------

10 Stability and Reactivity

- Reactivity corresponds to 10.3
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known

11 Toxicological Information

- Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	LD50	2410 mg/kg (mouse) (OECD 401)
Dermal	LD50	2764 mg/kg (Rabbit)
9004-78-8 Phenol, ethoxylated		
Oral	LD50	500-2000 mg/kg (Rat)
Dermal	LD50	2140 mg/kg (Rabbit)
134737-05-6 Diquarternary polydimethylsiloxane		
Oral	LD50	>5000 mg/kg (Rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

Safety Data Sheet according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

Trade name: VehiclePro Klear!Glow RM 894

(Contd. of page 6)

12 Ecological Information

· Toxicity

· Aquatic toxicity:

112-34-5 2-(2-butoxyethoxy)ethanol

LC50/96 h	1300 mg/l (Lepomis macrochirus)
EC10/16 h	1170 mg/l (Pseudomonas putida)
EC50/24 h	2850 mg/l (Daphnia magna) (DIN 38412)
NOEC	>100 mg/l (Desmodesmus subspicatus)

1474044-71-7 1-propanaminium, 2-hydroxy-N-(2-hydroxypropyl) -N-N-dimethyl, diesters with vegetable oil fatty acids, methyl sulfates

LC50/96 h	>10 mg/l (Cyprinus carpio)
EC50/48 h	>8.6 mg/l (Daphnia magna)
EC50/72 h (static)	1.2 mg/l (Pseudokirchneriella subcapitata)
EC50	100 mg/l /6 d (STP)
NOEC	0.686 mg/l /35 d (Pimephales promelas)
	1 mg/l /21 d (Daphnia magna)
	0.39 mg/l /72 h (Pseudokirchneriella subcapitata) (OECD 201)

1335203-21-8 Imidazolium compounds, 2-C17-unsatd.-alkyl-1-(2-C18-unsatd. amidoethyl)-4,5-dihydro-N-methyl, Me sulfates

LC50/96 h	1.8 mg/l (Leuciscus idus) (OECD 203)
EC50/48 h	0.105 mg/l (Daphnia magna) (OECD 202)
EC50	564 mg/l /3 h (STP) (OECD 209)
ErC50/72h	>0.4 mg/l (Pseudokirchneriella subcapitata)
NOEC	>0.145 mg/l /21 d (Daphnia magna) (OECD 211)

134737-05-6 Diquaternary polydimethylsiloxane

LC50/96 h	30.8 mg/l (Danio rerio) (OECD 203)
EC50/48 h	>200 mg/l (Daphnia magna) (OECD 202)
ErC50/72h	0.49 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC (dynamic)	0.313 mg/l /(72 h) (Pseudokirchneriella subcapitata) (OECD 201)

· Persistence and degradability No further relevant information available.

· Degree of elimination:

112-34-5 2-(2-butoxyethoxy)ethanol

OECD 301C	80-90 % (28 d)
OECD 301E	>70 % (28 d)
OECD 302B	100 % (28 d)

1474044-71-7 1-propanaminium, 2-hydroxy-N-(2-hydroxypropyl) -N-N-dimethyl, diesters with vegetable oil fatty acids, methyl sulfates

OECD 301F	>60 % (28 d)
OECD 311	>60 % (60 d)

(Contd. on page 8)

Safety Data Sheet
according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

Trade name: VehiclePro Klear!Glow RM 894

(Contd. of page 7)

9004-78-8 Phenol, ethoxylated	
OECD 301F	79 % (28 d)
OECD 311	>60 % (60 d)

- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **COD-value:** 720.000 mg/l
- **General notes:**

The product does not contain organically bounded halogens (AOX-free).

The product does not contain organic complexing agents.

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.
- **Uncleaned packaging:**
- **Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
- **Recommended cleansing agents:** Water, if necessary together with cleaning agents.

14 Transport information

· UN-Number	
· ADG, IMDG, IATA	Void
· UN proper shipping name	
· ADG, IMDG, IATA	Void

(Contd. on page 9)

Safety Data Sheet according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

Trade name: VehiclePro Klear!Glow RM 894

(Contd. of page 8)

· Transport hazard class(es)	
· ADG, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· ADG, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**

7732-18-5	water
112-34-5	2-(2-butoxyethoxy)ethanol
9004-78-8	Phenol, ethoxylated
67-63-0	propan-2-ol
57-55-6	Propylene glycol
64-19-7	acetic acid
134737-05-6	Diquarternary polydimethylsiloxane
25265-71-8	Dipropylene glycol (isomer unspecified)
18479-58-8	Dihydromyrcenol
76-22-2	1,7,7-Trimethylbicyclo[2.2.1]heptan-2-one
19009-56-4	2-Methyldecanal
7785-53-7	d-.alpha.-Terpineol
5989-27-5	(R)-p-mentha-1,8-diene
110-41-8	2-methylundecanal
112-54-9	Lauric aldehyde
470-82-6	eucalyptol
54464-57-2	1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone
58567-11-6	Formaldehyde cyclododecyl ethyl acetal
67634-00-8	allyl (3-methylbutoxy)acetate
68039-49-6	2,4-Dimethyl-3-cyclohexen-1-carboxaldehyde
2216-51-5	L-menthol
34902-57-3	Oxacyclohexadecen-2-on

(Contd. on page 10)

Safety Data Sheet according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

Trade name: VehiclePro Klear!Glow RM 894

(Contd. of page 9)

14073-97-3	I-Menthone
56973-85-4	1-(5,5-Dimethyl-1-cyclohexen-1-yl)pent-4-en-1-one
4180-23-8	trans-Anethole
91-64-5	Coumarin
556-67-2	octamethylcyclotetrasiloxane
112-12-9	2-Undecanone
97-53-0	Eugenol
140-67-0	Estragole

Standard for the Uniform Scheduling of Medicines and Poisons

112-34-5	2-(2-butoxyethoxy)ethanol	S5
64-19-7	acetic acid	S2, S5, S6
76-22-2	1,7,7-Trimethylbicyclo[2.2.1]heptan-2-one	S5, S6
470-82-6	eucalyptol	S6
91-64-5	Coumarin	S4
97-53-0	Eugenol	S5, S6
97-54-1	isoeugenol	S5, S6
94-59-7	safrole	S6, S10
106-24-1	geraniol	S6
5392-40-5	Citral	S5

Australia: Priority Existing Chemicals

None of the ingredients is listed.

National regulations

Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
A product information sheet can be provided if requested.

Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

Contact:

Regulatory Affairs

Tel.: +49-7195-14-0

productsafety.management.de@karcher.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 11)

Safety Data Sheet
according to WHS Regulations

Date of issue: 07.11.2025

Version number 5

Revision: 14.10.2025

Trade name: VehiclePro Klear!Glow RM 894*(Contd. of page 10)*

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute toxicity - oral – Category 4: Acute toxicity – Category 4
Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2
Eye damage/irritation – Category 1: Serious eye damage/eye irritation – Category 1
Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

· *** Data compared to the previous version altered.**

· 0·011-045·0 RM894/2 2·861

— AU —